Centauro 100/32



Technical Specification

All specifications subject to change without prior notice






Features:

Width(transport): m 2,55
Length (transport): m 11,2
Height (transport): m 3.1
Shredder Type: FTR 1000

Screenunit: m 3.20x1.00 double deck

Weight: Kg 24.000

Genset Diesel JCB 448 121KW at 1500 rpm Alternator130KVA




Advantages:

- High productivity up to 120 t / h
- Quick installation
- Remote control with cable.
- Single genset in order to minimize fuel consumption
- Engine Electrical, to optimize performance in order to reduce fuel consumption
- Engine Electrical, to ensure a consistent performance of screening regardless of the environmental conditions of work.
- Big distance between the two screening decks (600mm) allows an easy maintainability.
- Optional to change speed on all the conveyors.
- Optional radio control wireless.
- Don't produce noise and air pollution
- Possibility to distribute electricity to the jobsite

Feeding Hopper:

Length: m 3.00 Width m 2.00 Capacity: m³ 3.00

Hydraulic Feed hopper extensions optional extra



All specifications subject to change without prior notice




Shredder:


Type of Shredder: FTR 1000 Feed opening: mm 1000x900

Rotor Knives: pcs 18 Rotor Knives width: mm 50

Electric motor: kW 30 (15+15)

Rotors speed: rpm 10





Overbelt Magnet:


Belt width: mm 650 Conveyor length: mm 1.660 Electric moto-reducer kW 1.5

Power: 420 Gauss at 200 mm

Screenunit:

Screen Area: m 3.20x1.00


Deck: n° 2 Electric motor: kW 4



All specifications subject to change without prior notice







Genset:

Diesel Engine: JCB 448 121 kW a 1500 rpm Alternator: M.E.C.C. ALTE 130 kVA

Tank capacities:

Hydraulic: I 85 Fuel: I 170

Side Conveyors:

Belt width: mm 500 Stockpile height: m 2.70÷ 3.30

Electric moto-reducer: kW 4

Hydraulically folding Dust reduction

Main Conveyor:

Belt width: mm 800 Electric moto-reducer: kW 5.5


Dust reduction

Tail Conveyor:

Belt width: mm 800 Stockpile height: m 2.70÷ 3.30

Electric moto-reducer:: kW 4

Hydraulically folding Dust reduction



Track Data:

Track length: mm 2920 Track width: mm 400

Hydraulic Motor:bosch Rexroth 28/60 cc

Gearbox: Trasmital Speed: 0,4÷0,8 Km/h

Control: Remote handset - Dual Speed


All specifications subject to change without prior notice




CAMS s.r.l.

OPTIONAL EXTRAS

Hydraulic Fingers:
Number of fingers n° 5
Number of Knife: n° 2/pcs. n° 2/pcs. n° 2/pcs. Number of Teeth:






Hydraulic Feed Hopper extensions:

Height: Lenght mm 750

Hydraulic setting Adjustment: Hydraulic Jack: N° 2

Hydraulic Jack: N° 3 Number of components



All specifications subject to change without prior notice






CENTAURO 100/32 AT WORK



CENTAURO 100/32 FOR SHIPPING



All specifications subject to change without prior notice



CAMS s.r.l.